

INFRARED THERMAL CAMERA PX300





TECHNOLOGY PRODUCTS

- 5.8" Capacitive Touch Screen
- HD 5MP Visual Camera
- IR Resolution 384x288
- View Finder & Large LCD Display
- Digital Zoom upto 8x

The SATIR PX-300 is a new generation handheld camera that has a new housing design for the industrial market. It features a 384x288 IR detector which will deliver a clear, crisp image to the end-user on the touch screen. It also has a 5MP digital camera which is useful when comparing thermal and digital images in reports. It has various connectivity options including, Wi-Fi, Bluetooth, HDMI, USB & 4G. It has a GPS function which is useful for reports to pinpoint the exact location images were taken. It has a wide temperature range of -20~650°C, up to 1500/2000°C upon request with account manager. It has four imaging modes which allows the end-user to select which best suits their application, these are IR/Digital/Duovision/PiP.

Key Features

- 384x288 Detector Resolution
- HD 5MP Digital Camera
- IR/Digital/Duo-vision/PiP
- Manual/Motorized/Auto Focus
- Bluetooth/WIFI/4G/USB/HDMI Transmission
- QR Code and Barcode Function
- GPS



Thermal Camera

- Detector type: 384x288 FPA, Uncooled microbolometer
- Thermal sensitivity: ≤0.04°C@30°C
- Spatial resolution: 0.66mRad
- FOV/Min. Focus distance: 24°x18°/0.30m
- Ergonomic Optical: 160°
- Spectral range: 7.5 µm~14 µm
- Frame rate: 30Hz
- Focus: Continuous LDM, One-shot LDM, Manual
- **Digital zoom:** x1, x2, x4, x8

Image presentation

- LCD display: Cover Glass Touch screen 5.8-inch, 1280 x 768 pixels
- Image mode: IR/CCD/Duo-vision/PiP
- Digital camera: HD 5MP
- Image enhancement: Yes

Image storage

- Type:32GB removable SD card
- Thermal Image Format: Standard JPEG, including measurement data, on memory card



Temperature measurement

- Measurement range: -20~650°C, up to 1500/2000°C(optional)
- Pseudo colour: 10 types including Iron, Iron-inverted, Grey, Greg-inverted
- **Analysis tool:** 10 movable spots, auto hot/cold/average, 10 area boxes, 5-line, isotherm, above, below, interval, alarm
- Accuracy: ±2°C or 2% of readings
- Measurement Correction: Emissivity, reflected temperature, relative humidity, object distance, offset, ambient

Environment specification

- Operating temperature range: -20°C~+55°C
- Ambient temperature range: -40°C~+70°C

Protective performance

- Encapsulation: IP54 (IEC 60529)
- Shock/Vibration: 25G/2G

Physical characteristics

- Weight: 1.6 KG
- **Dimension**: 210x119x174 mm

Power system

- Battery type: Lithium-ion battery
- Battery operating time: 3hours

Ports

• Output ports: Type-C USB, Bluetooth, WIFI, HDMI

Other features

• Viewfinder: Yes, 1024x768 pixels

• Lensidentification: Yes

• Super Resolution: Yes

• Illuminator: Yes, Automatic

• Laser pointer: Yes

• Laser ranging: Yes, 40 meters

• QR code and Bar code: Yes

• Video record: Yes

• Auto shutdown & Sleep mode: Yes

• GPS:Yes

• 4G:Yes

 Accessories: Hardcase, Hand strap, Protective Bag, Cables, Adaptor, Manual Book, Software SATIR Report Pro

Please be aware specifications can vary from time to time



Over 35 Years of Industry Experience

At Technology Products, we are a premier manufacturer and supplier of cutting-edge Electrical Testing, Measuring, and Safety Equipment, with capabilities up to 800 KV. Our expertise extends beyond equipment design and manufacturing to offering solutions for Electrical Safety and Testing—from concept to commissioning. Trust us to deliver precision, safety, and innovation in every project.





Get in Touch

Address

<u>Technology Products,</u> <u>Plot 114, Udyog Vihar, Phase 4,</u> <u>Gurgaon, Haryana 122015, India</u>

Phone
+91 98188 45710

WhatsApp +91 98188 45710

Email info@tpindia.co.in