

SOFT DISCHARGE RODS





TECHNOLOGY PRODUCTS

- Controlled Discharging
- Light Weight
- Smooth and Glossy Finish
- Customised Lengths Available
- Type Tested as per IS & IEC



Non-Linear Carbon Discharge Resistor Type Discharge Rods are used to discharge dead systems having limited fault levels and also to discharge the static & induced charges in the dead system or equipment, particularly in cables, transformers, reactors, large busbar systems, switchgears etc. The earthing lead is made up of special highly flexible braided copper cable with transparent or bright coloured sheath. Copper Hook of 4" diameter of ½" thick copper rod & Earth End Clamp of special alloy are provided.

- Main Insulation: 'F' Class to IS, BS & IEC Specifications
- **Dimension of Main Pole & Extension Handles:** 25.5mm ID, 30.70mm OD, 1500mm(main pole), 1650mm(extension handle)

Lengths of Insulated Sticks

- Main Pole Only: 1.5m
- Main Pole + 1 Extn. Handle: 3.0m
- Main Pole + 2 Extn. Handle: 4.5m
- Main Pole + 3 Extn. Handle: 6.0m
- Main Pole + 4 Extn. Handle: 7.5m
- Customised lengths also available



Over 35 Years of Industry Experience



At Technology Products, we are a premier manufacturer and supplier of cutting-edge Electrical Testing, Measuring, and Safety Equipment, with capabilities up to 800 KV. Our expertise extends beyond equipment design and manufacturing to offering solutions for Electrical Safety and Testing—from concept to commissioning. Trust us to deliver precision, safety, and innovation in every project.





Get in Touch

Address

<u>Technology Products,</u> <u>Plot 114, Udyog Vihar, Phase 4,</u> <u>Gurgaon, Haryana 122015, India</u>

Phone
+91 98188 45710

WhatsApp +91 98188 45710

Email info@tpindia.co.in